

TERRAIN TAMER



4WD PRODUCTS

Electric Winch 12000lb Water Resistant

www.Pro4wd.cz



> Specifications

- Rated line pull 12000lbs (5443kgs)
- Gear reduction ratio 230:1
- Motor Series wound (Input power)
5.4kw/7.2hp (12DC)
5.3kw/7.1hp (24DC)
- Control Remote switch, 12ft (3.7m) lead
- Gear train 3 stage planetary gear train
- Clutch Sliding ring gear
- Braking action Automatic screw cone braking action
- Fairlead 4-way Roller fairlead
- Remote control Through control box and switch
- Battery 12/24 volt battery
- Battery leads 2 gauge, 72" (1.83mm)
- Overall dimensions 22.80" (L) x 6.30" (W) x 10.6"(H),
580 (L) mm x 160 (W) mm x 268 (H) mm
- Drum Size 2.50" (D) x 8.90"(L), 63(D) mm x 226(L) mm
- Cable 13/32" (D) x83.70"(L), 10.2mm (D) x 25.50m (L)
- Weight 93.3lbs (42.3 kg)
- Mounting bolt pattern 10" x 4.5" (254mm x 114.3mm) 4-M10
- Warranty 3 year warranty



Tips & Techniques DVD included

PART NUMBER
TEW12000WP

DESCRIPTION
ELECTRIC WINCH
WATER RESISTANT



> Duty Cycle

LINE SPEED AND MOTOR CURRENT (FIRST LAYER)

Line Pull	Line Speed		Motor Current	
	Ft/min (m/min)		Amps (Max)	
Lbs (kgs)	12V DC	24V DC	12V DC	24V DC
0	22.3(6.8)	23(7)	100	60
4000 (1814)	13.1(4)	13.8(4.2)	220	130
7000 (3175)	9.8(3)	10.8(3.3)	330	170
12000 (5443)	5.8(1.8)	7.4(2.3)	450	220

LINE PULL AND CABLE CAPACITY

Layer	Rated Line Pull	Total Rope On Drum
	Lbs(kgs)	Ft(m)
1	12000(5443)	17.5(5.3)
2	9563(4338)	39.5(12.0)
3	7949(3606)	64.9(19.8)
4	6801(3085)	84.0(25.5)

To view a demonstration of this product visit our website terraintamer.com